

## 5V

### Description:

The 5V Crimp is a factory formed corrugated metal roof and wall panel that provides a traditional metal panel appearance for Commercial & Industrial applications. The 5V panel is mechanically fastened with exposed fasteners. The panel is available in a wide variety of materials and finishes including Kynar 500®/Hylar 5000® pre-finished G-90 Galvanized Steel and Aluminum, Copper, Anodized and Mill Finish Aluminum, and Galvalume.



### Materials & Thickness:

- ▶ Galvanized & Galvalume 29-26ga  
Unpainted / SColor +

### Method of Application:

1. 5V Panel may be installed in a non-sequential pattern over a solid substrate or open framing.

### Precautions:

1. Oil canning is not a cause for rejection.
2. Exercise caution when lifting, moving, transporting, storing or handling metal to avoid possible physical damage.

### Accessories:

We offer a full line of accessories that compliment this profile.

#### PRODUCT DATA

|                            |                                       |
|----------------------------|---------------------------------------|
| Panel Type:                | Commercial / Industrial / Residential |
| Panel Interlock:           | Over Lapping                          |
| Tapered Panels:            | No                                    |
| Radiused:                  | No                                    |
| Standard Panel Surface:    | Smooth                                |
| Optional Panel Surface:    | No                                    |
| Substrate:                 | Solid Substrate or Open Framing       |
| Minimum Recommended Slope: | 3:12                                  |

#### PANEL SIZE

|                    |      |
|--------------------|------|
| Panel Face Width:  | 24"  |
| Min. Panel Length: | 48"  |
| Max. Panel Length: | 480" |